

**ON THE HUNT FOR AN ALL-AROUND REGULATOR?  
CHECK OUT THE HARRIS **MODEL 25GX**.**

The Harris Model 25GX is a legendary American classic. It is a medium to heavy duty with a time-proven design that is built for those who want an economical, high-performance regulator. It features larger, easier to read gauges and an ergonomic adjusting knob that also shields the adjusting mechanism from contaminants.

The 25GX is designed to be the next generation workhorse of the Harris industrial regulator line.



**ORIGIN:**

Made in the European Union in an ISO 9001 and 14001 certified facility

**QUALITY:**

100% tested, 100% of the time

**SAFETY:**

Meets or exceeds all relevant industry standards - ISO 2503 (cylinder pressure and flow control regulators) and ISO 5171 (pressure gauges)

**CAPACITY:**

Medium to heavy duty

**RELIABILITY:**

One-piece encapsulated seat prevents damaging particles from entering the high pressure valve seat

**DESIGN:**

Ergonomic modern design allows for precise pressure adjustments. Knob offers additional protection by shrouding the bonnet housing. Outlet angle designed for LP cylinder clearance.

**DELIVERY PRESSURES:**

0 - 1,5; 0 - 4; 0 - 10; 0 - 15 bar

**PRESSURE REGULATION:**

Excellent pressure regulation from full to empty cylinder

**WARRANTY:**

7 year

**25GX**  
MODEL



**SINGLE-STAGE CYLINDER REGULATOR**

MODEL SHOWN:  
**25GX-1.5-AC**

**APPLICATIONS:**

- ▶ Heavy duty, large, strong regulator for the professionals

**FEATURES:**

- ▶ Maximum inlet pressure of 230 bar
- ▶ Enough flow to cut up to 400 mm steel
- ▶ Large Ø 70 mm diaphragm stabilizes working pressure
- ▶ Forged brass body for maximum strength
- ▶ Durable chrome-plated bonnet
- ▶ One-piece encapsulated seat design with internal filter and PTFE (Teflon®\*) seat
- ▶ Side entry
- ▶ 7 year warranty



MODEL NO.	GAS	MAX INLET PRESSURE (bar)	DELIVERY PRESSURE (bar)	MAX AIR FLOW (m³/h)	DELIVERY PRESSURE GAUGE (bar)	SUPPLY PRESSURE GAUGE (bar)
25GX-1.5-AC	Acetylene	25	0 - 1,5	52	0 - 2,5	0 - 40
25GX-4-LP	Propane	25	0 - 4	25	0 - 6	0 - 40
25GX-D4-OX	Oxygen	230	0 - 4	112	0 - 6	0 - 315
25GX-D4**	Argon, CO <sub>2</sub> , Nitrogen, Air, Methane	230	0 - 4	112	0 - 6	0 - 315
25GX-AD-4**	Helium, Hydrogen	230	0 - 4	112	0 - 6	0 - 315
25GX-D10-OX	Oxygen	230	0 - 10	170	0 - 16	0 - 315
25GX-D10**	Argon, CO <sub>2</sub> , Nitrogen, Air, Methane	230	0 - 10	170	0 - 16	0 - 315
25GX-AD-10**	Helium, Hydrogen	230	0 - 10	170	0 - 16	0 - 315
25GX-D15-OX	Oxygen	230	0 - 15	275	0 - 25	0 - 315
25GX-D15**	Argon, CO <sub>2</sub> , Nitrogen, Air, Methane	230	0 - 15	275	0 - 25	0 - 315
25GX-AD-15**	Helium, Hydrogen	230	0 - 15	275	0 - 25	0 - 315

\* Teflon® is a registered trademark of The Chemours Company

\*\*The regulator is available for all the listed gases. When ordering always specify gas.

